

PRINTRONIX
AUTO ID

ODV-2D

THERMAL PRINTER VALIDATOR

**COMPLIANT
VALIDATION**

**EASY
COMMUNICATION**

**DEPENDABLE
DESIGN**





Eliminate expensive compliance fees by producing 100% accurate barcodes, 100% of the time.

The ODV-2D is the industry's first affordable, fully integrated solution with the ability to print and validate 1D and 2D barcodes. Built on the robust T8000 printer platform, ODV-2D includes a built-in data validator that grades barcodes to ISO standards and stores a detailed report of each transaction. Our exclusive technology reads each barcode, overstrikes the entire label of a rejected barcode, and reprints a new label. The ODV-2D delivers accelerated ROI by eliminating charge backs and fines for non-conformance labels. Advanced features allow it to integrate easily and quickly into existing applications.



COMPLIANT VALIDATION & PRODUCTIVITY

- Validates full suite of 1D & 2D barcodes with up to 50 barcodes per label
- Prints up to 8ips with full validation, grading & compliance reporting
- Grades to ISO standards including Quiet Zone & Check Sum errors
- Full label back-up and overstrike
- Barcode "GPS" dynamically locates barcode, orientation & improved throughput
- Most affordable, fully integrated solution on the market



EASY COMMUNICATION & NETWORKING

- Most extensive suite of printer emulations in the industry
- PrintNet Enterprise Auto ID provides global or enterprise wide network access, control, update and reporting
- Supports Ethernet or WiFi & includes 802.11 ac for faster communication & improved range
- Extensive and scalable security solutions



DEPENDABLE DESIGN

- Built on the proven design of our most robust printer, the T8000
- Dual motor design for outstanding print quality & productivity
- Large 3.4" color display panel with intuitive menu and navigation keys
- Intelligent heat management for longer printhead life outstanding print quality even at top speeds

TIRED OF REJECTED SHIPMENTS AND COMPLIANCE FEES?

With a global increase in regulatory compliance standards and fines, it is more important than ever to ensure your products are labeled correctly with accurate barcodes. ODV-2D addresses these requirements with the ability to validate up to 50 barcodes per label INCLUDING 2D Barcodes.

The ODV-2D reads and grades every label based on ISO standards. When ODV-2D rejects a barcode, it strikes out the entire label and reprints it without operator intervention. At the end of the day you can generate a report directly from the printer with data on every label printed and graded. Archive that data and you'll never pay compliance fees again!



WE BUILT A COMPLETE SOLUTION SO YOU DON'T HAVE TO

With the introduction of the ODV-2D we've eliminated the need for companies to piece together their own solutions from separate printers and validators. ODV-2D offers the industry's first affordable, fully integrated solution with the ability to print and validate **1D and 2D barcodes**. The ODV-2D is built on the proven design of our most robust printer, the T8000.

MANAGE YOUR ENTIRE ENTERPRISE FROM A SINGLE LOCATION

PrintNet Enterprise Auto ID (PNE) gives you the ability to dynamically record, archive and generate reports of scanned barcode data for each printer. With the addition of our robust printer management tool, you can pull reports for your entire enterprise as well as monitor and configure printers from anywhere in the world. You can also designate events and be alerted to printer issues via email, pager or mobile phone alerts. PrintNet Enterprise is available at no charge with the purchase of an ODV-2D printer.

WHAT IS THE DIFFERENCE BETWEEN A VALIDATOR AND VERIFIER?

Not much with the ODV-2D. A verifier provides a technical analysis to internationally agreed upon standards (ISO). In order to meet the footprint and productivity requirements of production environments, the design of the ODV-2D has been refined and improved to optimize productivity and space requirements. As a result, the ODV-2D does not require an external device to grade 2D barcodes. By stitching the barcode image together at production speeds, the ODV-2D validation process grades and validates barcode information based upon ISO verification standards. The ODV-2D is a state-of-the-art printer validator that does not require additional accessories in order to offer compliant label output.



ODV-2D

SPECIFICATIONS



PRODUCT BENEFITS

- * High performance ARM Cortex-A9
- * Die-cast aluminum frame w/metal door
- * Transfer and direct printing
- * 4" model configuration
- * Premium Asian and Andale font support
- * State-of-the-art WiFi connectivity
- * Available in 203 DPI and 300 DPI
- * Dual motor ribbon drive system
- * 512MB RAM / 128MB Flash Memory
- * 4-32 GB SD memory card capability
- * ENERGY STAR Certified

PRINTER SPECIFICATIONS

| | |
|------------------|----------------------------------|
| Max Print Speed | 8 IPS @ 203 DPI; 8 IPS @ 300 DPI |
| Print Method | Transfer and Direct |
| Resolution | 203 DPI or 300 DPI |
| Max. Print Width | 4.1" (104mm) |
| Printer Memory | 512MB RAM / 128MB Flash |

MEDIA SPECIFICATIONS

| | |
|--------------------------|--|
| Media Type | Roll or Fan-Fold Labels, Tags, Paper, Film, Tickets |
| Min. Media Width | 1" (25.4mm) |
| Max. Media Width | 4.5" (114.3mm) |
| Min. Media Length | 0.25" / 1.0" (Continuous/Tear-Off) / 0.5" (Peel-Off) |
| Max. Media Length | Up to 99" |
| Media Thickness | 0.0025" (0.0635mm) to 0.010" (0.254mm) |
| Media Roll Core Diameter | 1.5" (37.5mm) to 3.0" (76mm) |
| Max. Media Roll Diameter | 8.0" (209mm) |
| Media Sensing | Gap, Mark, Advanced Gap, Advanced Notch |

RIBBON SPECIFICATIONS

| | |
|--------------------|-----------------------|
| Ribbon Type | Wax, Wax/Resin, Resin |
| Min. Ribbon Width | 1" (25.4mm) |
| Max. Ribbon Width | 4.5" (114.3mm) |
| Max. Ribbon Length | 625 Meters |

MEDIA HANDLING MODES

| | |
|----------|--------------------------------------|
| Standard | Continuous, Tear-Off Strip, Tear-Off |
| Options | Peel-Off, Rewind |

PHYSICAL CHARACTERISTICS

| | |
|-----------------|-------------------|
| Width | 11.7" (297.2mm) |
| Height | 13" (330.2mm) |
| Depth | 20.5" (520.7mm) |
| Printer Weight | 37 lbs. (16.7Kg.) |
| Shipping Weight | 46 lbs. (20.8Kg.) |

PRINTER LANGUAGE

| | |
|-----------------------------|--|
| IGP Languages | PGL/VGL/ZGL/TGL/IGL/STGL/DGL/IEGL/MGL |
| Line Printer Plus Languages | P-Series + XQ, Proprinter, Serial Matrix, Epson |
| Job Control Languages | PJL, XML, and PTX-SETUP |
| Optional Languages | IPDS TN5250/TN3270 PDF Level 1.7, Postscript Level 3 |

COMMUNICATION AND CONNECTIVITY / INTERFACE

| | |
|------------------------|--|
| Standard Interface I/O | Serial RS232, USB, and Ethernet 10/100Base T |
| Optional Interface I/O | Parallel, WiFi (802.11 b/g/n 2.4GHz) (802.11 a/n/ac 5GHz), GPIO |
| WiFi Security Protocol | WEP 40/128bit, WPA Personal (TKIP), WPA2 Personal (AES/CCMP), EAP-PEAP, EAP-TTLS, PEAPv0/EAP-MSCHAPv2, EAP-TLS Security Certificates |

BARCODE VALIDATION

| | |
|----------------------------|-------------------------------|
| Barcode Type | 1D & 2D |
| Read Technology | 5MP Camera |
| Barcode GPS | Yes |
| Max Barcodes per label | 50 |
| Overstrike Area | Full label |
| Validate Min. X-Dimension | 10 mils |
| Validate Max. X-Dimensions | 60 mils |
| Barcode Orientation | 0°, 90°, 180°, 270° |
| Barcode Grading | A, B, C, D, F |
| Grading Report | Yes |
| Validation Standard | Based on ISO/IEC 15415, 15416 |
| Enterprise Network Support | Yes w/PNE |

OPERATING ENVIRONMENT

| | |
|-----------------------|---|
| Operating Temperature | Direct Thermal w/o accessories: 23° to 104°F (-5° to 40°C) Thermal Transfer: 40° to 104°F (5° to 40°C) |
| Operating Humidity | 20-85% Non-Condensing |
| Storage Temperature | 23° to 140°F (-5° to 60°C) |
| Storage Humidity | 5 to 85% Non-Condensing |

POWER REQUIREMENT

| | |
|------------|--------------------------------------|
| Line Input | Auto Range 90 - 264 VAC (48 - 62 Hz) |
|------------|--------------------------------------|

REGULATORY COMPLIANCES

| | |
|---------------|-------------------------|
| Emissions | FCC, CE, CCC |
| Safety | cTUVus, CE |
| Environmental | RoHS, WEEE, Energy Star |

BARCODES SUPPORTED FOR VALIDATION

| | |
|-------------|--|
| 1D Barcodes | Code 39, Code 93, Interleaved 2/5, Code 128, EAN 8 & 13, UPC-A, UPC-E, EAN UPC add-ons, Codabar |
| 2D Barcodes | *PDF417, PDF417 Truncated, PDF417 Micro, DataMatrix, DataMatrix ECC 200, QR, AZTEC * Call to confirm, all barcodes listed may not be available initially |

FONT, GRAPHIC SUPPORT

| | |
|---------------------------------|---|
| Graphic Formats | PCX, TIFF, BMP, PNG |
| Font Technologies | Intellifont, TrueType, Unicode |
| Standard Fonts | OCRA, OCRB, Courier, Letter Gothic, CG Times, CG Triumvirate/Bold/Condensed |
| Asian Fonts (Optional SD card) | Simplified Chinese, Japanese, and Korean |
| Andale Fonts (Optional SD card) | Simplified Chinese, Traditional Chinese, Korean, Japanese |
| PDF/ PostScript Level 3 | 35 Fonts |

REMOTE MANAGEMENT SOFTWARE

| | |
|---------------------------|---|
| PrintNet Enterprise Suite | Enterprise Grade Remote Management Solution |
|---------------------------|---|

OPTIONS AND ACCESSORIES

| | |
|--------------------------------------|--------------------------------------|
| * WiFi 802.11 a/b/g/n/ac (US/EU/CAN) | * Rewind |
| * Parallel Port Card | * Peel & Present |
| * GPIO | * Premium Asian Font Cards |
| * TN5250 | * Premium Andale Font Cards |
| * PDF/PostScript | * QCMC (SD Quick Change Memory Card) |
| * IPDS | |



Contact your local Printronix Auto ID authorized reseller.

PRINTRONIX
AUTO ID

printronixautoid.com



© 2017 Printronix Auto ID Technology, Inc. All rights reserved. Printronix Auto ID Technology, Inc. and all product names, numbers and logos are trademarks or registered trademarks of Printronix, Inc. Product appearance and/or specifications are subject to change without notice. Windows® is a registered trademark of Microsoft Corporation™ in the United States and other countries. All other trademarks, product names and company names and logos herein, are the property of their respective owners. (9/17)